



Model: ST-10RF

Energy Consumption Guide (based on a 24-hour time period)

| | | |
|----------------------|--------------------|-----------------------|
| Ambient Temp (Below) | Top +38 °F (+3 °C) | Bottom +0 °F (-18 °C) |
| 77 °F (25 °C) | 188 WHR | 314 WHR |



SUNSTAR Features

- AC/DC Dual input voltage
- Top: refrigerate; Bottom freeze or refrigerate
- Reversible door
- Defrost: Top: automatic; Bottom: manual
- Precise temperature control in each compartment
- Interior fan for even cool down
- Fast cooling system
- Available in multiple colors
- Marine duty compressors
- Adjustable shelving
- Quiet run design

Technical Details

| | |
|--|---|
| Total Volume | 278 Liters / 9.8 Cu Ft – Top 6.6 / Bottom 3.2 |
| Cooling System | Direct Cooling |
| Temperature Control | Mechanism |
| Rated Operating Voltage | 12V10.6V – 17V / 24V21.3 – 31.5V; 115VAC |
| Fuse Rating (A) | 30 / 15 Amp 12/24 VDC |
| Typical Power Draw | 55 Watt 12/24V 4.3/2.2Amp |
| Refrigeration Agent | R600A |
| Inside Product Dimension (in) Top / Bottom | W 18 / H 30.3 / D 20.5; W 17.5 / H 17 / D 20.25 |
| Outside Product Dimension (in) | W 23.5 / H 60 / D 26.25 |
| Carton Box Dimension (in) | W 25.25 / H 60.75 / D 27.4 |
| Weight Per Carton / Net Weight | 165 lb / 148 lb |
| Performance Warranty | 2 Year |